





**[www.multiplo.gr](http://www.multiplo.gr)**



Multiplo system .....	7
Textile installation .....	9
Wall Single Side - 20mm .....	12
Wall built-in Single side - 32mm .....	13
Wall Single Side - 34mm .....	14
Double Side - 45mm .....	15
Double Side - 45mm ECO .....	17
Back LED Wall Single Side - 49mm .....	18
Side LED Wall Single Side - 80mm .....	19
Side LED Double Side - 80mm .....	20
Side LED Double Side - 120mm light .....	21
Side LED Double Side - 120mm .....	22
Side LED Single Side - 150mm .....	23
Side LED Double Side - 150mm .....	24
Light Corner .....	25
Heavy Corner .....	26
Hinge .....	28
Extra Profiles - Accessories - Bases .....	30
LED Side lighting .....	32
LED Back lighting .....	34
Spot lights .....	35
Waterproof Power Supplies .....	36
Textiles - Silicone tape .....	37
Storage - Carrying cases .....	38



## About us

EVIN Intzoglou has been established in 1989 specializing in visual communication products. We have the fullest range of Stands & Displays available for Below The Line promotional activities. Our range includes ready to sell models, while for special needs there is the possibility of special construction. The company also has a modern, large-format printing department. In our vertical production unit, which includes design, production and assembling, we develop products that match every need and meet the highest requirements for modern aesthetics and ultimate functionality.

Over the past 5 years, our company has been building the innovative "Multiplo" visual communication system.

## About Multiplo

A visual communication system that meets every communicational need, from P.O.S. display to an entire exhibition stand. Ideal for events, visual merchandising or wherever there is a need for signage or decoration. It highlights high-quality images and strengthens your communication needs. The products are available illuminated or not.

## Natural Anodized Aluminium Profiles

Frame of construction from 10 different aluminum profiles depending on the use. Very durable, extendable, repairable. It can be painted in any RAL colour or nickel.

## Printing

Digital UV printing on a waterproof, elastic, flame-retardant textile, with silicone tape sewn around the perimeter. Very easy to replace without tools or trained personnel.

## LED Lighting

Intense and homogeneous lighting that highlights prints. Low power consumption, long life. Dimmable.







### File preparation for printing on textile

- A 0,8 cm contour is added to the printing area. Both height and width of the file should be 1,6 cm larger.
- E.g. For a frame 100 x 150 cm, the final printing file should be 101,6 x 151,6 cm
- Take care not to place any logos or text near the edge to make sure it won't be cut out.
- Minimum file resolution should be 150 dpi to avoid pixelated result.

Acceptable file example



Not acceptable file example





# **Aluminium Profiles**

## Wall Single side 20mm

**ID:** PRF/0049

**Rod length:** 3,05m


**Profile depth:** 19,6mm

**Profile weight:** 360gr/m

**Use:** Single side, wall mounted

**Profiles to be paired with:**

PRF/0071, PRF/0050, PRF/0051



## Connection



## Supporting Parts



PART/0005



PART/0043



PART/0068



PART/0115

## Wall built-in Single side 32mm

Suitable for wall fitted LED Lightboxes  
For backlighting, minimum 45mm depth is required.  
For side lighting, minimum 80mm depth is required.  
The interior of the installation should always be white.

**ID:** PRF/0014

**Rod length:** 3m



**Profile depth:** 32mm

**Profile weight:** 255gr/m


**Use:** Single side, wall fitted,  
LED illuminated or not

**Illumination:** Side or Back

**Profiles to be paired with:** PRF/0071



## Connection



Section - Installation on wall guide

## Supporting Parts



PART/0005



PART/0043



PART/0068



PART/0115

## Wall Single side 34mm

**ID:** PRF/0010



**Rod length:** 3,05m

**Profile depth:** 34,2mm


**Profile weight:** 565gr/m

**Use:** Single side, wall mounted

**Profiles to be paired with:** PRF/0071



## Connection



Connection using PART/0005



Connection using PART/0039 x 2 pcs.



Part for installation on wall

## Supporting Parts



PART/0005



PART/0039



PART/0045



PART/0068



PART/0115

Double side  
45mm

**ID:** PRF/0037



**Rod length:** 3,05m

**Profile depth:** 45mm


**Profile weight:** 860gr/m

**Use:** Double side, free standing or  
suspending

**Profiles to be paired with:** PRF/0071,  
PRF/0020



## Connection



## Supporting Parts



PART/0005



PART/0068



PART/0083  
for BASE/0011



PART/0084  
for BASE/0015



BASE/0011



BASE/0015



BASE/0028  
left



BASE/0029  
right

## Double side 45mm

**ID:** PRF/0068



**Rod length:** 3,05m

**Profile depth:** 45mm

**Profile weight:** 1059gr/m

**Use:** Double side, free standing or  
suspending

**Profiles to be paired with:** PRF/0071,  
PRF/0020



## Connection



## Supporting Parts



PART/0005



PART/0068




PART/0083  
for BASE/0011



PART/0084  
for BASE/0015



PART/0126



PART/0143



BASE/0011



BASE/0015



BASE/0028  
left



BASE/0029  
right



**ID:** PRF/0064



**Rod length:** 3,05m

**Profile depth:** 45mm

**Profile weight:** 460gr/m

**Use:** Double side free standing or  
suspending

**Profiles to be paired with:** PRF/0071



## Connection



## Supporting Parts



PART/0005



PART/0068



PART/0083  
for BASE/0011



PART/0084  
for BASE/0015



PART/0043



BASE/0031



BASE/0032

## Back LED Wall Single side 49mm


**ID:** PRF/0062

**Rod length:** 3,05m


**Profile depth:** 49mm

**Profile weight:** 710gr/m

**Use:** Single side, LED illuminated  
wall mounted



## Connection



## Supporting Parts



PART/0005



PART/0068

## Side LED Wall Single side 80mm

**ID:** PRF/0065



**Rod length:** 3,05m

**Profile depth:** 80mm

**Profile weight:** 859gr/m

**Use:** Single side, LED illuminated  
(2nd side not illuminated), wall mounted

**Profiles to be paired with:** PRF/0071



### Connection



### Supporting Parts



PART/0005



PART/0039



PART/0045



PART/0068



PART/0126

Side LED  
Double side  
80mm

**ID:** PRF/0061


**Rod length:** 3,05m

**Profile depth:** 80mm


**Profile weight:** 1023gr/m

**Use:** Double side, LED illuminated  
free standing or suspending

**Profiles to be paired with:** PRF/0071



## Connection



Connection using PART/0039 x 2 pcs

## Supporting Parts



PART/0039



PART/0045



BASE/0015

**Side LED  
Double side  
120mm light**

**ID:** PRF/0054



**Rod length:** 3,05m

**Profile depth:** 120mm


**Profile weight:** 1328gr/m

**Use:** Double side, LED illuminated,  
free standing or suspending

**Profiles to be paired with:** PRF/0071



## Connection




## Supporting Parts



PART/0092



PART/0093



BASE/0023



BASE/0015

**ID:** PRF/0057



**Rod length:** 3,05m

**Profile depth:** 120mm


**Profile weight:** 2298gr/m

**Use:** Double side, LED illuminated,  
free standing or suspending

**Profiles to be paired with:** PRF/0071



## Connection



Connection using PART/0010 x 2 pcs

## Supporting Parts




PART/0005



PART/0110



PART/0111



PART/0112



BASE/0023



BASE/0015

**Side LED**  
**Single side**  
**150mm**

**ID:** PRF/0006

**Rod length:** 3,05mm

**Profile depth:** 150mm

**Profile weight:** 2215gr/m

**Use:** Single side, LED illuminated  
(2nd side not illuminated),

free standing or suspending

**Profiles to be paired with:** PRF/0071



**Connection**



**Supporting Parts**



PART/0005




PART/0068



BASE/0023



BASE/0015



## Side LED Wall Double side 150mm

**ID:** PRF/0067B

**Rod length:** 3,05m

**Profile depth:** 150mm


**Profile weight:** 2100gr/m

**Use:** Double side, LED illuminated  
free standing or suspending

**Profiles to be paired with:** PRF/0071



### Connection




### Supporting Parts



PART/0143



PART/0144



PART/0112



PART/0068



PART/0110



PART/0111



BASE/0023



BASE/0015




**ID:** PRF/0058

**Rod length:** 3,05m

**Profile weight:** 686gr/m

**Use:** Light corner, free standing or  
suspending cubes, LED illuminated or not


**Profiles to be paired with:** PRF/0014



## Supporting Parts



PART/0113



PART/0114



PART/0111

## Heavy corner



**ID:** PRF/0046

**Rod length:** 3,10m



**Profile weight:** 1370gr/m

**Use:** Corner, free standing or  
suspending cubes, LED illuminated or not

**Profiles to be paired with:** PRF/0014,  
PRF/0071, PRF/0068



## Connection




## Supporting Parts



PART/0005



PART/0043



PART/0061


**ID:** PRF/0050 & PRF/0051

**Rod length:** 2,80m

**Profile weight:** 622gr/m & 625gr/m

**Use:** Single side

**Profiles to be paired with:** PRF/0049  
PRF/0071



## Supporting Parts



PART/0005



PART/0043




PART/0042




# Parts

## Extra Profiles Parts Bases



**ID:** PRF/0071  
**Rod length:** 3,05m  
**Section dimensions:** 38,1x19,5mm  
**Profile weight:** 515gr/m  
**Use:** Support beam




**ID:** PRF/0020  
**Rod length:** 3m  
**Profile weight:** 83gr/m  
**Use:** Cap for PRF/0068 & PRF/0071




**ID:** PART/0041  
**Use:** Clasp for connecting PRF/0071



**ID:** BASE/0015  
**Dimensions:** 45x4,5cm  
**Thickness:** 6mm  
**Weight (pair):** 1,8Kg  
**Use:** Metal base for non LED 45mm (PRF/0068), LED 120 & 150mm (PRF/0054 & PRF/0057)  
 Grainy powder coating RAL 9006  
 Rubber footings



**ID:** BASE/0023  
**Dimensions:** 50x6cm  
**Thickness:** 10mm  
**Weight (pair):** 4Kg  
**Use:** Metal base for LED 120mm (PRF/0057), LED 150mm (PRF/0006)  
 Grainy powder coating RAL 9006  
 Rubber footings



**ID:** BASE/0011  
**Dimensions:** 45x6cm  
**Thickness:** 8mm  
**Weight (pair):** 4Kg  
**Use:** Side metal base for non LED 45mm (PRF/0068)  
 Grainy powder coating RAL 9006  
*\*PART/0083 needed for installation*



**ID:** BASE/0028 & BASE/0029

**Dimensions:** 26x21,5x6cm

**Thickness:** 6mm

**Use:** Side metal base (left or right) for use on Multiplo expo booths using PRF/0068. Grainy powder coating RAL 9006 .



**ID:** BASE/0031

**Dimensions:** 35x5cm

**Thickness:** 8mm (14mm including rubber footings)

**Use:** Anodized aluminium base with rubber footings on both ends. For Multiplo panels, LED or not.



**ID:** BASE/0032

**Dimensions:** 30x5cm

**Thickness:** 8mm (14mm including rubber footings)

**Use:** Anodized aluminium base with rubber footings on both ends. For Multiplo panels, LED or not.

## LED Side lighting



### Side LED module

ID: LED/0003

Pack of 20, side lighting.

**Voltage - Power:** 12V - 2,1W

**Color temperature:** 6500K

**Luminosity:** 170lm

**Protection class:** IP65

**Instructions:** Install on profile's side,  
10 pcs/m, max frame width 1m. Install on both sides.  
Max of 20 can be used in a row (series circuit).



### Side LED bars

ID: LED/0004

**Length:** 22cm

3 lenses for side lighting

**Voltage - Power:** 24V - 7,9W

**Color temperature:** 6500K

**Luminosity:** 610lm

**Protection class:** IP60

**Instructions:** Install on profile's side,  
1 pc every 25cm. In frames with max width of 1,5m, install on 2 sides.  
In frames with max width of 3m, install on 4 sides. Max of 10 can be used  
in a row (series circuit). Can be paired with LED/0005 & LED/0010.



### Side LED bars

ID: LED/0005

**Length:** 44cm

6 lenses for side lighting

**Voltage - Power:** 24V - 15W

**Color temperature:** 6500K

**Luminosity:** 1200lm

**Protection class:** IP60

**Instructions:** Install on profile's side,  
1 pc every 50cm. In frames with max width of 1,5m, install on 2 sides.  
In frames with max width of 3m, install on 4 sides. Max of 5 can be used  
in a row (series circuit). Can be paired with LED/0004 & LED/0010.



### Side LED bars

ID: LED/0010

**Length:** 94cm

13 lenses for side lighting

**Voltage - Power:** 24V - 27.36W

**Color temperature:** 6500K

**Luminosity:** 2600lm

**Protection class:** IP60

**Instructions:** Install on profile's side,  
1 pc every 100cm, In frames with max width of 1,5m, install on 2 sides.  
In frames with max width of 3m, install on 4 sides. Max of 3 can be used  
in a row (series circuit). Can be paired with LED/0004 & LED/0005.





**Side LED bars**

**ID:** LED/0008

**Length:** 47cm

9 lenses for side lighting with DC connector.

**Voltage - Power:** 24V - 11W

**Color temperature:** 6500K

**Luminosity:** 990lm

**Protection class:** IP60

**Instructions:** Install on profile's side,

1 pc every 50cm, max frame width of 1m. Install on 2 sides.

Max of 5 can be used in a row (series circuit). Can be paired with LED/0009.



**Side LED bars**

**ID:** LED/0009

**Length:** 96cm

18 lenses for side lighting with DC connector.

**Voltage - Power:** 24V - 22W

**Color temperature:** 6500K

**Luminosity:** 1980lm

**Protection class:** IP60

**Instructions:** Install on profile's side,

1pc every 1m, max frame width of 1m. Install on 2 sides.

Max of 3 can be used in a row (series circuit). Can be paired with LED/0008.



**Side LED bars**

**ID:** LED/0013B

**Length:** 46cm

10 lenses for side lighting with DC connector.

**Voltage - Power:** 24V - 15.6W/pc

**Color temperature:** 6500K

**Luminosity:** 1750lm

**Protection class:** IP20

**Instructions:** Install on profile's side,

1 pc every 50cm, max frame width of 1m. Install on 2 sides.

Max of 4 can be used in a row (series circuit). Can be paired with LED/0014B.



**Side LED bars**

**ID:** LED/0014B

**Length:** 94cm

20 lenses for side lighting with DC connector.

**Voltage - Power:** 24V - 31.2W/pc

**Color temperature:** 6500K

**Luminosity:** 3440lm

**Protection class:** IP20

**Instructions:** Install on profile's side,

1pc every 1m, max frame width of 1m. Install on 2 sides.

Max of 2 can be used in a row (series circuit). Can be paired with LED/0013B.

## LED Back lighting



### Back LED module

ID: LED/0006

Pack of 20, backlighting

**Voltage - Wattage:** 24V - 1,44W / 2 pcs

**Color temperature:** 6500K

**Luminosity:** 150lm

**Instructions:** Install on lightboxes' back. Suggested for small sized lightboxes.

Max of 20 can be used in a row (series circuit). Can be cut every 2 pcs.



### Back LED bars

ID: LED/0011

**Length:** 48cm

7 lenses for backlighting

**Voltage - Wattage:** 12V - 5,9W

**Color temperature:** 6500K

**Luminosity:** 647lm

**Instructions:** Install on lightboxes' back.

Max of 4 can be used in a row (series circuit).

Place each line of bars up to 25cm to the next one (midpoint to midpoint) for 80mm depth & 14.3cm for 49mm depth Lightbox.

Can be paired with LED/0012.



### Back LED bars

ID: LED/0012

**Length:** 93cm

13 lenses for backlighting

**Voltage - Wattage:** 12V - 11W

**Color temperature:** 6500K

**Luminosity:** 1201lm

**Instructions:** Install on lightboxes' back.

Max of 2 can be used in a row (series circuit).

Place each line of bars up to 25cm to the next one (midpoint to midpoint) for 80mm depth & 14.3cm for 49mm depth Lightbox.

Can be paired with LED/0011.



### 50 LED silver

ID: SPOT/0002

**Power - Voltage:** 11W / 100-240VA

**Color temperature:** 4200K

**Luminosity:** 1100lm

1m cable. Plus 2,5m extension available.

Unique part designed for easy installation on backdrop (PRF/0037) included.



### 116 LED silver

ID: SPOT/0003

**Power - Voltage:** 25W / 100-240VA

**Color temperature:** 4200K

**Luminosity:** 2600lm

1m cable. Plus 2,5m extension available.

Unique part designed for easy installation on backdrop (PRF/0037) included.



### Halogen silver

ID: SPOT/0001


**Power - Voltage:** 150W / 230VA

**Color temperature:** 3000K


**Luminosity:** 1000lm

1m cable. Plus 2,5m extension available.

Unique part designed for easy installation on backdrop (PRF/0037) included.



part included for easy installation on backdrop



## Waterproof power supplies



**ID: PART/0116**  
**Voltage - Current:** 12V/2A  
**Power:** 24W  
 LED DC power supply  
**Input:** 90-264VAC  
**Protection class:** IP67  
 Protection against short circuit, overcurrent and overvoltage.

**ID: PART/0117**  
**Voltage - Current:** 24V /1A  
**Power:** 24W



**ID: PART/0100**  
**Voltage - Current:** 12V/5A  
**Power:** 60W  
 LED DC power supply  
**Input:** 90-264VAC  
**Protection class:** IP67  
 Protection against short circuit, overcurrent and overvoltage.

**ID: PART/0107**  
**Voltage - Current:** 24V /2,5A  
**Power:** 60W



**ID: PART/0101**  
**Voltage - Current:** 12V/8,3A  
**Power:** 99,6W  
 LED DC power supply  
**Input:** 90-264VAC  
**Protection class:** IP67  
 Protection against short circuit, overcurrent, overvoltage and overtemperature.

**ID: PART/0108**  
**Voltage - Current:** 24V /4,2A  
**Power:** 100,8W



**ID: PART/0102**  
**Voltage - Current:** 12V/10A  
**Power:** 120W  
 LED DC power supply  
**Input:** 180-277VAC  
**Protection class:** IP67  
 Protection against short circuit, overcurrent, overvoltage and overtemperature.

**ID: PART/0109**  
**Voltage - Current:** 24V /6A  
**Power:** 144W



**ID: PART/0118**  
**Voltage - Current:** 12V/16A  
**Power:** 192W  
 LED DC power supply  
**Input:** 200-264VAC  
**Protection class:** IP67  
 Protection against short circuit, overcurrent, overvoltage and overtemperature.

**ID: PART/0119**  
**Voltage - Current:** 24V /8,3A  
**Power:** 199,2W



**ID: PART/0120**  
**Voltage - Current:** 24V/14,4A  
**Power:** 320W  
 LED DC power supply  
**Input:** 90-305VAC  
**Protection class:** IP65  
 Protection against short circuit, overcurrent, overvoltage and overtemperature.



**ID: PART/0121**  
**Voltage - Current:** 24V/20A  
**Power:** 480W  
 LED DC power supply  
**Input:** 90-305VAC  
**Protection class:** IP67  
 Protection against short circuit, overcurrent, overvoltage and overtemperature.



**ID:** PART/0124

**Voltage - Current:** 24V/1,25A  
**Power:** 30W

**ID:** PART/0122

**Voltage - Current:** 24V/4,17A  
**Power:** 100W

**ID:** PART/0132

**Voltage - Current:** 12V/2,5A  
**Power:** 30W

**ID:** PART/0134\*

**Voltage - Current:** 12V/8,34A  
**Power:** 100W

Slim power supply

**Input:** 180-264VAC

Protection against short circuit, overcurrent and overvoltage.

\*There is no protection for PART/0134.

**ID:** PART/0125

**Voltage - Current:** 24V /2,55A  
**Power:** 60W

**ID:** PART/0123

**Voltage - Current:** 24V /6,25A  
**Power:** 150W

**ID:** PART/0133

**Voltage - Current:** 12V /5A  
**Power:** 60W



**Block-out textile**

**Dimensions (per roll):** Length 50m, width 160, 260 & 320cm.

**Use:** Suitable for digital UV, sublimation & latex printing.

**Backside color:** grey

**Backlit textile**

**Dimensions (per roll):** Length 50m, width 160, 260 & 320cm.

**Use:** Suitable for digital UV, sublimation & latex printing.

Fire - retardancy certification: CLASS 1/B1  
according to NEN 6065:1991/A1:1997



**Silicone tape**


**ID:** PART/0015

**Coil dimensions:** Length of 100m & 250m

**Rubber dimensions:** 14x3mm.

**Use:** For sewing around the textiles.

## Storage Carrying Cases



**Cardboard box unprinted or with MULTIPLO illumination**

**ID:** CARTONBOX/0001 & CARTONBOX/0002

**Dimensions:** 120x25x25cm & 170x25x25cm

**Use:** Suitable for storing and carrying LED or non LED backdrops



**Fabric bag**

**ID:** M/BAG/0003

**Dimensions:** 170x25x25cm

**Use:** Suitable for storing and carrying LED or non LED backdrops. Straps for carrying and internal small pocket included.



**Trolley case**

**ID:** M/BAG/0008

**Dimensions:** 121x29x20cm

**Use:** Suitable for storing and carrying LED or non LED backdrops. Protecting dividers, straps for fixing and internal pocket included.



**Fabric case**

**ID:** M/BAG/0009

**Dimensions:** 106x26x13cm

**Use:** Suitable for storing and carrying LED or non LED backdrops. Fixing straps and small internal pocket included.



**Fabric case**

**ID:** M/BAG/0004, M/BAG/0006

**Dimensions:** 106x14x93cm, 91x11x80cm

**Use:** Suitable for storing and carrying promostands.

by **EVIN** Intzoglou®

N. Notara 23, 17343  
Ag. Dimitrios, Athens  
**T** 210 9753140,  
210 9753111  
**F** 2109753950  
**E** [info@evin.gr](mailto:info@evin.gr)  
[www.evin.gr](http://www.evin.gr)  
[www.multiplo.gr](http://www.multiplo.gr)